



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	31.01.17	OT

Electrical
Current rating: 1Amps/contact max.
Contact resistance: ≤ 20mΩ/contact
Isolation resistance: ≥ 1000MΩ at V=100V
Withstanding Voltage: 300V AC/minute

Material
Contact: Brass
Isolator: High Temperature, Thermoplastic UL94V-0

Operating temperature: Gold plated: -55°C to +105°C
 Tin plated: -40°C to +105°C

order information

A127103	xx	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	No. of Insulators	Insulator Hight	Packaging	Dimension	Special Customer	
01~50	01= gold flash	1=1pcs	10= H= 1.00mm	A= bag	A/ B		
	xx= on request	2=2pcs	15= H= 1.50mm	xx= on request	A/ B/ C		
		xx=on request	17= H= 1.70mm		xx= on request		
			20= H= 2.00mm				
			25= H= 2.50mm				
			xx= on request				

	BRCONNECTORS		Single Row Pin Header Straight Type			
	PROJECTON					
	DATE	31.01.2017	Customer Drawing-No.:			
	DRAWN	OT	Drawing-No.: 2160748			
	CHECKED	BR				
APPROVED	BR	UNIT:	SCALE:	SIZE:	A4	

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.