

4


3

2

1

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR



Technical Spezifications

Insulator: Black glass filled polyester PPS-GF30-FR  
 Flammability: UL 94V-0  
 Sleeve: Brass CuZn36Pb3(C36000)  
 Mating Pin Ø: 0.45mm / 0.48 mm  
 Mechanical Life: Min. 500 cycles  
 Rated Current: 3 A  
 Contact Resistance: Max. 10mΩ  
 Dielectric Steength: Min. 1000V<sub>RMS</sub>

order information

AP254107	xx	xx	xx	xx
No. of Positions	Plating Option	Packaging	Special Customer	
01~40	01= gold flash 100= tin	C= tube xx= on request		
		xx= on request		



Single Row Precision Pin Header Straight Type

PROJECTON	
DATE	30.03.2017
DRAWN	MR
CHECKED	BR
APPROVED	BR

Customer Drawing-No.:	
Drawing-No.:	2160964
UNIT:	mm
SCALE:	
SIZE:	A4

Tolerance:  
 X. ±0.50  
 .X ±0.30  
 .XX ±0.20  
 .XXX ±0.05  
 X\* ±2"

