

RoHS
REACH
compliant


REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR

Technical Specifications

Insulator: Black glass filled polyester PPS+GF30
 Flammability: UL 94V-0
 Sleeve: Brass CuZn36Pb3(C36000)
 Mating Pin Ø: 0.76mm
 Mechanical Life: Min. 500 cycles
 Rated Current: 3 A
 Contact Resistance: Max. 10mΩ
 Dielectric Strength: Min. 1000V_{RMS}
 Coplanar SMD Terminations: Max. 0.1mm (measured on 25mm long connectors)

order information

AP254154	-	xx	xx	xx	-	xx
No. of Positions	Plating Option	Packaging	Special Customer			
04~64	01= gold flash	F= tape&reel with cap				
	100= tin	xx= on request				
		xx= on request				



	Dual Row Precision Pin Header Straight SMT Type		
	PROJECTON		
	DATE	30.03.2017	
	DRAWN	MR	
	CHECKED	BR	
APPROVED	BR		
	UNIT:	SCALE:	SIZE:
	mm		A4

Tolerance:
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 .XXX ±0.05
 X* ±2"