

4



3

2

1

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR



Technical Spezifications

Insulator: Black glass filled polyester PPS+GF30  
 Flammability: UL 94V-0  
 Sleeve: Brass CuZn36Pb3(C36000)  
 Mating Pin Ø: 0.76mm  
 Mechanical Life: Min. 500 cycles  
 Rated Current: 3 A  
 Contact Resistance: Max. 10mΩ  
 Dielectric Steength: Min. 1000VRMS  
 Coplanariny SMD  
 Terminations: Max. 0.1mm (measured on 25mm long connectors)

order information

AP25415S	-	xx	xx	xx	xx
No. of Positions	Plating Option	Packaging	Special Customer		
02-64	01= gold flash	F= tape&reel with cap			
	100= tin	xx= on request			
		xx= on request			



BRCONNECTORS

Single Row Precision Pin Header Straight SMT Type

Tolerance:  
 X. ±0.50  
 .X ±0.30  
 .XX ±0.20  
 .XXX ±0.05  
 X\* ±2"

PROJECTON	
DATE	30.03.2017
DRAWN	MR
CHECKED	BR
APPROVED	BR

Customer Drawing-No.:  
 Drawing-No.: 2160989

UNIT: mm SCALE: SIZE: A4

