

4



3

2

1

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR



Technical Spezifications

Insulator: Black glass filled polyester PPS+GF30
 Flammability: UL 94V-0
 Sleeve: Brass CuZn36Pb3(C36000)
 Mating Pin Ø: 0.76mm
 Mechanical Life: Min. 500 cycles
 Rated Current: 3 A
 Contact Resistance: Max. 10mΩ
 Dielectric Steength: Min. 1000V_{RMS}
 Coplanariny SMD
 Terminations: Max. 0.1mm (measured on 25mm long connectors)


order information

AP254157	xx	xx	xx	xx
No. of Positions	Plating Option	Packaging	Special Customer	
03~64	01= gold flash 100= tin xx= on request	F= tape&reel with cap xx= on request		



Single Row Precision Pin Header Straight SMT Type

Tolerance:
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 .XXX ±0.05
 X* ±2"



PROJECTON		
DATE	30.03.2017	Customer Drawing-No.:
DRAWN	MR	Drawing-No.: 2160991
CHECKED	BR	
APPROVED	BR	
	UNIT: mm	SCALE: SIZE: A4